

Wolf® XT-602, XT-604, XT-606 ATEX ZONE 0 FLOOD BANKS



Certification & Compliance

- The Flood Bank Stand includes Wolflite XT Rechargeable Zone 0 Handlamps (XT-75), CE marked to the ATEX Directive and IECEx Certified.
- It provides up to 2,100 lumens of light.
- This powerful light is for use in a Zone 0,2 and 2 hazardous area.
- T4 temperature class
- The system offers excellent performance and reliability.

Technical Specifications

- Incorporates Wolflite XT Rechargeable Zone 0 Handlamps (XT-75)
- Ultra-bright high power LED with light output up to 2,100 lumens
- Available in 2, 4, or 6 handlamp configurations per bank
- Can be mounted on a tripod (sold separately) or placed on the ground
- Switchable spot and flood beam options
- Battery duration: up to 7.5 hours (full power) / 15 hours (power-save)
- Built-in state of charge indicator for each handlamp
- IP67 dust and watertight rating
- Mains chargers provided; charging must be done in a safe area

Stands sold separately, compatible with all Wolflite XT Handlamp models

Standards



Ex-Proof (ATEX)



IECEx



CE 0598

TECHNICAL DETAILS

Product Reference	XT-602	XT-604	XT-606
Product Description	ATEX Zone 0 Flood Bank		
Handlamp Configuration	x 2	x 4	x 6
Stand Material	Stainless Steel		
Handlamp Holder Material	Impact Resistant Thermoplastic, Electrostatic Non-Hazardous 'Snap-in/Snatch-out' Function		
Dimensions	340 mm L x 197 mm W x 451 mm H	340 mm L x 352 mm W x 451 mm H	340 mm L x 507 mm W x 451 mm H
Weight - Stand/Holders Only	2.6 Kg	3.6 Kg	4.5 Kg
Weight - With Handlamps	5 Kg	8.4 Kg	11.7Kg
Total Light Output	700lms	1400lms	2100lms
Handlamps & Chargers	Includes Stand with Handlamp Holders only attached, Wolflite XT Rechargeable Zone 0 Handlamps (XT-75) and a separate Quick Charger with Mains Adaptor 100-254V AC (XT-200H - for use in safe area only) for each handlamp.		

