Wolf® ATEX 250VA Transformer



LL-114/T4, LL-214/T4, LL-221/T4, LL-133/T4, LL-233/T4, LL-234/T4

The Wolf ATEX 250VA Transformer is a professional ex-proof power unit designed to maximize safety while powering temporary lighting and electrical systems in hazardous areas. Offered by IST Safety Ltd, the official distributor of Wolf, this unit steps down high voltage to safe operating levels such as 24V or 110V, protecting personnel from electrical shock risks, particularly in wet and metallic conductive environments.

Certified for Zone 1/21, the transformer features a robust, impact-resistant, and corrosion-proof GRP (Glass Reinforced Polyester) enclosure, ensuring reliable performance in the harshest industrial conditions. Its compact and portable design provides significant ease for installation and logistics across all field applications, from refineries to tank cleaning operations.

Usage areas

- **Tank Cleaning and Maintenance:** Safely powering low-voltage lighting systems in confined spaces.
- **Oil & Gas:** Establishing temporary electrical lines in refineries and petrochemical plants according to ex-proof standards.
- **Marine:** Safe power distribution for blasting, painting, and welding works in ship holds and ballast tanks.
- **Chemical Industry:** Acting as a portable power station in sites with flammable and explosive vapors.

- CE marked and IECEx certified to the ATEX Directive.
- Maximum output: 250VA at ambient temperatures up to +55°C.
- Group II, Category 2 equipment for use in:Zones 1 & 2: Potentially explosive gases, vapors, and mists (temperature class T4).Zones 21 & 22: Potentially explosive dusts (maximum surface temperature of 130°C).
- Enclosure options:GRP or Stainless Steel, sealed to IP66 for use in wet and dusty environments. Stainless steel outer protective skid for added strength and easier handling during temporary

installations.

- Construction:Robust, durable, compact, and portable.Fully flexible for different configurations to meet specific hazardous area requirements.
- For Output Power ≤ 250VA: Ex d e IIC T4 Gb - Ex t IIIC T130°C Db (-20°C ≤ Ta ≤ +55°C)

Warranty and Technical Support

- **Warranty:** 2-year manufacturer's warranty.
- **Official Support:** Original spare parts and professional technical service are provided through IST Safety Ltd, the official distributor of Wolf in Turkey.

Standards

Ex-Proof (ATEX)

IECEx

TECHNICAL DETAILS

- T4 temperature class with max operating temperature of +55°C
- Strong and durable construction
- Easy to transport and portable design
- Supports a range of voltages: 230V or 110V to 24V, and 230V to 110V
- Has 4 x ATX socket outlets
- Comes with a 15m SY cable and ATX plug
- Available with CEAG, STAHL, and Marechal plug options
- Powers temporary ambient and task lighting

ATEX 250VA TRANSFORMER						
Product Reference	**LL-114/T4**	**LL-214/T4**	**LL-221/T4**	**LL-133/T4**	**LL-233/T4**	**LL-243/T4**
Product Description	GRP			Stainless Steel		

110V:24V	230V:24V	230V:110V	110V:24V	230V:24V	230V:110V
CODE	For Output Power ≤ 250VA: Ex d e IIC T4 Gb - Ex t IIIC T130°C Db (-20°C ≤ Ta ≤ +55°C)				
Type of Protection	'e' increased safety, 'd' flameproof				
Area of Classification(Gas)	Zones 1 and 2 Gas Groups IIA, IIB and IIC				
Temperature Class (Gas)	T4				
Area of Classification (Dust)	Zones 21 and 22 Dust Groups IIIA, IIIB and IIIC				
Max. Surface Temperature (Dust)	T130°C				
Ambient Temperature	-20°C to +55°C				
Certificate	ATEX - LCIE02ATEX6248X IECEX - LCI 04.0016X			ATEX-LCIE02ATEX6118X IECEX - LCI 11.008X	
Enclosure	Glass reinforced polyester (GRP) enclosure, stainless steel skid			Marine grade (316L) stainless steel	
Power	250VA				
Volts In	110V ac +6% - 10%	230V ac +6% - 10%		110V ac +6% - 10%	230V ac +6% - 10%
Input Cable	15m SY cable 2.5mm² with ATX 110V / 230V 2P+E plug fitted as standard				
Volts Out	24V		110V	24V	110V

Socket Arrangement & ConfIguratIon	4 output sockets ATX 110V / 24V 2P+E as standard	
	2 sockets on each unit side	
DImensIons	504 x 465 x 285 mm (L x W x H)	512 x 562 x 260 mm (L x W x H)
Ingress ProtectIon	IP66	
WEIGHT	21 Kg	28 Kg

What is ATEX Lighting?

What is ATEX and what does exproof mean? The **ATEX directive** is a set of European Union standards that define the safety requirements for equipment used in hazardous areas with explosive atmospheres. **Exproof** (Explosion-proof) refers to protection methods designed to prevent explosions by inhibiting the formation of sparks or electrical arcs in environments containing flammable gases, dust, or vapors. To ensure life and property safety in industrial facilities, the use of **ATEX-certified exproof devices** is a legal requirement.

What is ATEX Zone Classification?

ATEX Zone coding is a technical classification based on the frequency and duration of the occurrence of an explosive atmosphere in a given area. While the terms **Zone 0, 1, and 2** are used for risks originating from gas, vapor, and mist; the codes **Zone 20, 21, and 22** are designated for environments containing combustible dust. This classification is a legal standard that determines the required Equipment Protection Level (EPL) for devices. Accurate zone identification both optimizes operational costs and minimizes occupational safety risks.

What is IECEx Certification? How Does it Differ from ATEX?

In addition to ATEX certification, some projects may also require the IECEx Certification System (International Electrotechnical Commission Explosive Atmospheres System) certification. IECEx is an internationally recognized conformity assessment system for equipment intended for use in explosive atmospheres.

While ATEX is a European Union directive and a legal requirement within the European market, IECEx is a globally accepted certification system, widely preferred in regions such as the Middle East, Asia, and Australia.

From a technical perspective, both ATEX and IECEx are based on similar standards (e.g., the EN/IEC 60079 series). However:

- ATEX is a mandatory legal directive, whereas
- IECEx is an international certification system (voluntary, but widely required)

Therefore, while ATEX certification may be sufficient for certain projects, international tenders or critical industries such as oil & gas often prefer or require products that are certified to both ATEX and IECEx standards.

The appropriate certification should be determined based on the project location, client requirements, and application area.